

MERIT Hg System Final Design Review

Hg Target System Operations

V.B. Graves

P.T. Spampinato

T.A. Gabriel

MERIT Collaboration Meeting

MIT Plasma Science & Fusion Center

Oct 5, 2005

Outline



- **Facility constraints**
- **System installation**
 - Components in TT2A
 - System assembly & alignment
- **Hg handling & filling**
- **Off-normal conditions**
- **System removal and decommissioning**
 - System disassembly
 - Hg drain
 - Prepare for shipment






Facility Constraints



- **No overhead lifting capability within tunnel**
- **Modularity required**
 - **Component footprint size limitation is 1.3m x 4.4m**
- **40cm step traversal required to enter TT2A**

Components into TT2A


- **Mobile crane used to lower equipment from ground level to pit floor**
- **Hilman rollers or on-board casters allow component transport**
- **CERN "turtle" available as needed**
- **Prefer to use cable ratchet to control travel down slope**




Installation Sequence Part 1 (Out-of-beam)





Transport Hg System




Remove Rollers




Transport Baseplate, Install Magnet



Remove Rollers, Level Magnet



Roll Hg System into Magnet




Add Rollers

OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY




Installation Sequence Part 2 (In-beam)


Roll System into Beam Line



Remove Rollers



Elevate & Tilt



- **Baseplate & magnet will go in beam line prior to Hg system**
- **Blocks under magnet end to provide adequate tilt**

Alignment to Beam



- **Fiducials assumed to be on magnet baseplate and Hg system secondary containment sleeve**
- **Gross alignment with Hilman rollers**
- **Fine alignment with baseplate alignment mechanisms for magnet & Hg cart**
- **Precision alignment using CERN beam locators**
 - May still require fine tuning after first few beam pulses
- **May need secondary/magnet interface bracket to prevent nozzle movement**

Hg Handling Issues




Properties, Safety Limits, Standards

- Atomic Weight: 200.59
- Boiling Point: 357 degree C
- Specific Gravity: 13.6
- Vapor Pressure: 0.0012 mm Hg
- Vapors: colorless, odorless
- Solubility: insoluble in water
- NIOSH/OSHA limits: 0.05 mg/m³, 10 h/day; 40 h/wk
 - *ORNL: 0.025 mg/m³, respirators at 0.012 mg/m³*

The Target Test Facility (TTF) - Basis For ORNL's Hg Handling Experience



- Full scale, prototype of SNS Hg flow loop
- 1400 liters of Hg
- Used to determine flow characteristics
- Develop hands on operating experience
- Assess key remote handling design issues



TTF Pump Room and Target Room

- **75 Hp centrifugal pump**
- **Nominal flow at 1450 liters/min (380 gpm)**
- **Completed several major equipment upgrades for piping and target configuration**



TTF Hg Loading

- **TTF vacuum pump was used to transfer Hg directly into the storage tank from 540+ flasks**
 - Peristaltic pump available as backup



Proper PPE Is Mandatory



- **Overalls, gloves, and overshoes are the minimum requirement for TTF loop maintenance**



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY



MERIT Collab. Mtg Oct 17-29, 2005



Operational Issues



- **Is special notification required at MIT for Hg operations for integrated systems testing**
 - The schedule shows a safety review and target test plan to be presented to MIT staff in Feb. 2006
- **Will CERN provide the third vapor monitor for sampling the tunnel environment?**
 - Who is responsible for monitoring the tunnel?
- **Will MIT and CERN provide support for repackaging the target equipment and Hg for delivery back to ORNL?**



Hg Loading



- A glove box could be required for unloading Hg at the completion of testing if refilling flasks is not permitted outside of the secondary containment
 - Consider use of snorkel near flasks in lieu of glove box



Hg Loading Operation



- Secondary containment cover remains installed
- Pump into sump tank
 - Air displaced from sump tank vented through secondary passive filtration
- Hg vapor control with snorkel
- Glovebox used if required

Inlet port



Filter Replacement

- Effectively requires breaching the secondary containment
- Filter pack will be covered by a plastic bag taped in place
- Snorkel will be placed adjacent to the filter
- Monitor # 3 will be used to sample air in the filter region



Estimate For Filter Lifetime



Saturation Pressure

$$\log P_{sat} = -3105.5 / T_{0K} + 4.9294 \quad (\text{bar})$$

Saturation Concentration

$$C_{sat} = 2.445 P_{sat} / T_{0K} \quad (\text{Kg}_{\text{Hg}}/\text{m}^3) \quad (P_{sat} \text{ mbar})$$


Ref. Quechsilber und seine Gefahren, Swiss government worker safety report, SBA No. 145, Luzern

- Flow Rate 110 cfm
- Temp. 25 °C
- Filter Effic. 99.0%
- Filter Weight 6 lbs
- Filter Satur. 12%
- Filter Life 185 hrs
 - Does not incl. reduction for humidity

Selected Off-Normal Events and Recovery

- We need to address credible off-normal occurrences and recovery
- 1. Small spill (1 ml) or vapor leak into the secondary containment verified by vapor monitors # 1 and # 2
 - Continue to operate to the expected limit of the filter lifetime based on the measured vapor concentration-analysis
 - Monitor for changes to vapor readings in the secondary enclosure
 - Monitor air in the tunnel for indications of vapor
 - if none, continue testing

Note: If only one monitor registers vapors – could be a false-positive; continue to operate if #3 reads $<0.0125 \text{ mg/m}^3$



Off-Normal Events (cont.)



2. Medium spill (100 ml) into secondary containment verified by vapor monitors # 1 and # 2

- Continue to operate to the expected limit of the filter lifetime based on measured vapor concentration-analysis
 - Monitor for any changes to vapor readings in the secondary enclosure
 - Monitor air in the tunnel for indications of vapor; if none, continue testing
 - If approaching limit of filter life consider connecting the snorkel to extend the time of operation, if that allows completion of the test program.


(Note: Connecting the snorkel may require a waiting period of one or more days for a safe activation level; therefore the snorkel may be already connected but not turned on.)

Off-Normal Events (cont.)



3. Full inventory spill into the secondary containment

- Monitor target instruments for clues to the source of leakage
 - Verify by checking sump tank level sensor, conductivity sensor, and nozzle pressure sensor
- Cease operations, wait for cool down to visually inspect
- Monitor air in the tunnel for indications of vapor
- Seal inlet and outlet vents on secondary enclosure
- Wait for additional cool down to permit hands on recovery and storage of Hg.



Off-Normal Events (cont.)



4. **Vapors detected outside of secondary containment by monitor # 3 - assume the secondary containment is breached or that the filter is saturated**
 - **Confirm with readings from #1 and #2 vapor monitors**
 - **If confirmed ... cease operations**
 - **If not confirmed ... continue operations**
 - **Monitor target instruments for clues to the source of leakage**
 - **verify by checking sump tank level sensor, conductivity sensor, and nozzle pressure sensor**
 - **Wait for cool down, visually inspect and sample local air**
 - **If levels are above safe limit (0.025 mg/m³ ??), inspect with full face mask-Hg respirator cartridges**
 - **Repair breach in enclosure if possible, pressure check, continue test operations**

CERN limit ?? mg/m³

OSHA limit 0.050 mg/m³

ORNL limit 0.025 mg/m³

TTF limit 0.0125 mg/m³

Miscellaneous Equipment For The Target System



Large Items	Small Items
Vacuum Cleaner – Dry	Merc-X Cleaning Solution
Snorkel	Sponges
2 Vapor Monitors	Plastic Buckets
Spare Filters (qty. TBD)	Plastic Pans
Glove Box	Gauze – roll
Vacuum Pump ?	Small Tools
	Vinyl Tape
	Herculite
	Plastic Bags – asst'd (1 gal. – 20 gal.)
	1-liter plastic bottles
	Lab Coats
	Tyvek Hooded Suits
	Nitrile Gloves
	Full Face Mask/Respirator Cartridges


Post-Experiment Operations



- **The target equipment (and the solenoid) will have neutron-induced activation**
- **Based on (H. Kirk 9/01/04)**
 - 200 pulses
 - 16×10^{12} protons/pulse (avg.)
 - 30 days of operation
 - **Contact dose rate on the iron exterior will be:**
 - after 1 hr 40 mrad/hr
 - after 1 day 21 mrad/hr
 - after 1 week 13 mrad/hr
 - after 1 mo. 5 mrad/hr
 - after 1 year 1 mrad/hr
 - **Sergei Striganov (FNAL) performing separate analysis**
- **Move experiment out of beam line several days after conclusion, minimizing operator time near equipment**

Hg Draining

- Extract Hg & prepare for shipment after several month cool-down
- CERN requirement that secondary containment not be opened during draining
- Will be trapped Hg in extraction tube, flex hoses, Hg cylinder, plenum



Disassembly Operations



- **ORNL will take back the Hg target system and the activated Hg and components**
 - Is hydraulic system and fluid activated, or can we adequately shield?
- **Hopefully other uses for system will emerge**