



Scintillating Fiber Analysis

March 18, 2009

Harold G. Kirk



TDS 2024B - 2:53:22 PM 10/31/2007



TDS 2024B - 4:04:39 PM 10/31/2007

Shot 8036
14 GeV
dt = 700 μ s
15Tp + 5Tp
0T
Target Out

Shot 8042
14GeV
dt = 700 μ s
15Tp + 5Tp
7T
Target Out

Analysis of 8036

No Beam Current Transformer

Integrated pulse heights

$$\text{Pump } 10.44V - (-0.8 \times 10^{-2})V = 10.45V$$

$$\text{Probe } 3.72V - (1.2 \times 10^{-1})V = 3.60V$$

Ratio:

Pump/Probe = 2.90 (3.2% difference from 3)

Analysis of 8042

Integrated SF pulse heights

$$\text{Pump } 12.60\text{V} - (-0.8 \times 10^{-2})\text{V} = 12.61\text{V}$$

$$\text{Probe } 4.92\text{V} - (1.9 \times 10^{-1})\text{V} = 4.73\text{V}$$

Current Transformer

Pump 706003 (au)


Probe 232730 (au)

Ratios:

Beam Current 3.03

SF 2.67 → 13.6% difference

Shot 17011



14 GeV

$dt = 80 \mu\text{s}$

4Tp + 4Tp

7T

Target In

Analysis of 17011

Integrated SF pulse areas

Pump 172.4×10^{-9} V-s

Probe 175.6×10^{-9} V-s

Current Transformer

Pump 187829 (au)

Probe 196504 (au)

Ratios:

Beam Current 0.956

SF 0.984 → 2.9% difference